



Art. 605100501

**!** Read the technical data before installing this product. Observe the general safety instructions. Failure to follow the instructions may result in damage to the unit, fire or other hazards. Use this product only in dry areas.

Input	Efficiency	85% @230V AC, Full load
	Voltage	200V AC - 240V AC
	Frequency	50/60Hz
	Current	0.22A max @230V AC, Full load
	Dimming voltage range	40-240VAC
Output	Power factor	> 0.99
	Current / Voltage / Power	4.2A / 12V DC / 50W
	Channels	1
	Voltage Tolereance	±5%
Function	Dimming mode	Leading edge (TRIAC) / Trailing edge (ELV)
Protection	Over temperature	Automatically turns off when above 80°
	Working temperature	20°-40°
Others	Storage temperature / Humidity	-40°-85°, 20-90% RH
	Tc	70°
	Material	Polycarbonate
	IP rating	IP41
	Lifetime	30.000h @tc:70°
	Warranty	3 years
	Switches	>15.000x
Dimensions	L73 x W37 x H24mm	

**L**

230V~50Hz / 0.22A

**N**

**N**

**Dimmable Electronic Transformer**

Dimbare elektronische transformator  
Dimmbarer elektronischer Transformator  
Transformateur électronique à intensité variable

**.tc**

**0-50W**

cosφ>0,99 Ta:40°C max. Tc:70°C max.

No. 605100501 / Made in China

**Schiefer Lighting** Pottenbakkerstraat 35 4871 EP  
Etten-Leur The Netherlands [www.spl-lighting.com](http://www.spl-lighting.com)

**SPL**

**CE UK CA**

**OUT**

12V - 420mA max.