

Dimmer compatibility LED



Good dimming. Some slight flickering in lower or higher levels may occur

Dimming is not very smooth and/or flickering during a non definite part of the dimming range may occur

Dimming not possible



Brand	Model	Туре	load	load type			low
BERKER	2873		20-500	RL	2	10	100
BUSCH-JAEGER	6523U		2-100	RLC	3	10	100
BUSCH-JAEGER	6513U	Tronic	40-420	RC	1	10	90
Calex	2483HC	LED	3-70W	RC		UNSUITABLE	
GIRA	226200		20-500	RL		UNSUITABLE	
INTERTEK	68.40.99.07.99	LED	5-150	RC	1	10	100
JUNG	1730DD	LED	3-60W	RLC	1	10	100
JUNG	1731DD	LED	3-100	RLC	1	10	100
KLEMKO	D-PAF-200	LED	1-200	RC	1	10	100
LEGRAND	7 525 60	LED	5-75	RLC	1	10	100
LEGRAND	48871	LED	1-150		1	10	100
LUMEO	T39.07	Triac	3-100	RL	1	10	100
PEHA	431 HAN LED	LED	06-60	RL	1	10	100
Schneider	SBD315RC	Tronic	20-315	RC	3	10	100
SPL	960000101	LED	5-200/300	RL/RC	1	10	100
TRADIM	2485H	LED	0-70	RC	1	10	100
TRADIM	2490HP-exop	Tronic	5-150	RC	2	10	100
TRADIM	2494-K-exop	Tronic	2x3-100	RC	2	10	100
TRONIX	215-131	LED	10-350	LED	2	10	100
YPHIX	D350EX	LED	5-350	RC	2	10	100
						10	

Information presented is meant to serve as a general guideline only. Tests were conducted on 1 single dimmer in our Laboratories. True 1:1 dimmer compatibility can only be determined onsite under actual conditions and within the final application. Results can differ from dimmer to dimmer of even the same type number and brand. Please contact your local representative or a recognized electrical installer if any additional information is required.

