



PROFESSIONAL  
LIGHTING

### L022413527

LED G4 T12x37mm 12V 135Lm 1W 2700K  
827 300° AC/DC Mat Niet Dimbaar

Huishoudelijk, G4



| General               |              |
|-----------------------|--------------|
| Eprel registration no | 1514020      |
| Socket                | G4           |
| Bulb shape            | T12          |
| Width                 | 12.00 mm     |
| Depth                 | 10.00 mm     |
| Height                | 37.00 mm     |
| Finish                | Frosted      |
| Colour                | Colourless   |
| Body material         | Polycarbonat |
| Lifespan              | 15000 hours  |
| Switches              | 50000        |
| Beam angle            | 300 °        |
| Dimmable              | No           |
| Degree of protection  | IP20         |
| Net weight            | 0.003 kg     |
| Warranty              | 2 years      |

| Energy                  |                |                |
|-------------------------|----------------|----------------|
| Operating voltage       | 12 V           |                |
| Volt                    | 12 V           |                |
| Frequency               | 50..60 Hz      |                |
| Watt                    | 1 W            |                |
| Current type            | AC/DC          |                |
| Power factor            | 1              |                |
| Energy efficiency class | E              |                |
| Energy consumption      | 1 W            |                |
| Replacement wattage     | 15 W           |                |
| Lamp efficacy           | 135.00         |                |
| LED                     |                |                |
| Filament LED            | No             |                |
| LED type                | SMD 2835       |                |
| Dimm type               | Non-Dim        |                |
| Number of leds / sticks | 12             |                |
| Colour consistency SDCM | SDCM6          |                |
| Dim to warm             | No             |                |
| Adjustable beam angle   | No             |                |
| Ordering details        |                |                |
| L022413527              | Quantity pc(s) | EAN            |
| Single package          | 1              | 8718739069831  |
| Inner carton            | 10             | 18718739069838 |
| Outer carton            | 100            | 28718739069835 |

| Light                       |        |
|-----------------------------|--------|
| Kelvin                      | 2700 K |
| Colour temp nr              | 827    |
| Stable lumen                | 135 lm |
| Color Rendering Index (CRI) | 80     |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

29-01-2025