



PROFESSIONAL
LIGHTING

L022940030

LED GU10 MR11 Glas 35x47mm 230V 160Lm
3W 3000K 830 40° AC Helder Dimbaar

Huishoudelijk, Spot GU10 MR11



General		Energy	
Epel registration no	831200	Operating voltage	230 V
Socket	GU10	Volt	220..240 V
Bulb shape	MR11	Frequency	50..60 Hz
Width	35.00 mm	Watt	3 W
Depth	35.00 mm	Current type	AC
Height	47.00 mm	Power factor	0.9
Finish	Clear	Energy efficiency class	G
Colour	Silver	Energy consumption	3 W
Colour housing	Silver	Lamp efficacy	53.33
Body material	Glass	LED	
Lifespan	30000 hours	Filament LED	No
Switches	15000	LED type	SMD
Beam angle	40 °	Dimm type	Trailing edge
Dimmable	Yes	Number of leds / sticks	5
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.029 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No

Light		Ordering details		
Kelvin	3000 K	L022940030	Quantity pc(s)	EAN
Colour temp nr	830	Single package	1	8718739060357
Stable lumen	200 lm	Inner carton	10	18718739060354
Lumen 90 cone	160 lm	Outer carton	100	28718739060351
Luminous intensity	270 cd			
Color Rendering Index (CRI)	82			

Remark

General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

14-03-2025