

L142901930

LED E14 Tube T29x118mm 230V 1050Lm
10W 3000K 930 360° AC/DC Opaal
Dimbaar

Huishoudelijk, Tubular Premium



| General | |
|-----------------------|--------------|
| Eprel registration no | 831263 |
| Socket | E14 |
| Bulb shape | T28 |
| Width | 29.00 mm |
| Depth | 29.00 mm |
| Height | 118.00 mm |
| Finish | Opal |
| Colour | White |
| Body material | Polycarbonat |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.058 kg |
| Warranty | 3 years |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 10 W |
| Current type | AC/DC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 10 W |
| Replacement wattage | 75 W |
| Lamp efficacy | 105.00 |

| LED | |
|-------------------------|---------------------------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 72 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|---------|
| Kelvin | 3000 K |
| Colour temp nr | 930 |
| Stable lumen | 1050 lm |
| Color Rendering Index (CRI) | 90 |

| Ordering details | | |
|------------------|----------------|----------------|
| L142901930 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739063846 |
| Inner carton | 10 | 18718739063843 |
| Outer carton | 100 | 28718739063840 |