



PROFESSIONAL  
LIGHTING

**L147225027**

LED E14 Filament Kogel G45x75mm 230V  
160Lm 2W 2700K 827 360° AC Helder  
Dimbaar

**Decoratief, Ball E14**



General		Energy																			
Epel registration no	765829	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	2 W																		
Depth	45.00 mm	Current type	AC																		
Height	75.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	2 W																		
Body material	Glass	Replacement wattage	17 W																		
Lifespan	15000 hours	Lamp efficacy	80.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L147225027</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739065369</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739065366</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739065363</td></tr></table>		L147225027	Quantity pc(s)	EAN	Single package	1	8718739065369	Inner carton	10	18718739065366	Outer carton	100	28718739065363						
L147225027	Quantity pc(s)			EAN																	
Single package	1			8718739065369																	
Inner carton	10			18718739065366																	
Outer carton	100			28718739065363																	
Kelvin	2700 K																				
Colour temp nr	827																				
Stable lumen	160 lm																				
Color Rendering Index (CRI)	82																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

08-09-2024