



L223864830

LED Ba22d Stick T38x108mm 95-265V
640Lm 7W 3000K 830 270° AC Opaal Niet-
Dimbaar

Marine & Industrie, Tubular VR 95-265V



General		Energy	
Epel registration no	831343	Volt	95..265 V
Socket	Ba22d	Frequency	50..60 Hz
Bulb shape	T38	Watt	7 W
Width	38.00 mm	Current type	AC
Depth	38.00 mm	Power factor	0.5
Height	108.00 mm	Energy efficiency class	F
Finish	Opal	Energy consumption	7 W
Colour	White	Replacement wattage	50 W
Colour housing	White	Lamp efficacy	91.43
Body material	Polycarbonat	LED	
Lifespan	25000 hours	Filament LED	No
Switches	15000	LED type	SMD 2835
Beam angle	270 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	12
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.038 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No
Light		Ordering details	
Kelvin	3000 K	L223864830	Quantity pc(s) EAN
Colour temp nr	830	Single package	1 8718739058231
Stable lumen	640 lm	Inner carton	10 18718739058238
Color Rendering Index (CRI)	82	Outer carton	50 28718739058235

