



PROFESSIONAL  
LIGHTING

## L227250827-1

LED Ba22d Filament Kogel G45x75mm 230V  
470Lm 4W 2700K 827 360° AC Helder  
Dimbaar

## Decoratief, Ball Ba22d



| General               |             | Energy                  |                           |
|-----------------------|-------------|-------------------------|---------------------------|
| Eprel registration no | 1191464     | Operating voltage       | 230 V                     |
| Socket                | Ba22d       | Volt                    | 220..240 V                |
| Bulb shape            | G45         | Frequency               | 50..60 Hz                 |
| Width                 | 45.00 mm    | Watt                    | 4 W                       |
| Depth                 | 45.00 mm    | Current type            | AC                        |
| Height                | 75.00 mm    | Power factor            | 0.92                      |
| Finish                | Clear       | Energy efficiency class | E                         |
| Colour                | Colourless  | Energy consumption      | 4 W                       |
| Body material         | Glass       | Replacement wattage     | 40 W                      |
| Lifespan              | 15000 hours | Lamp efficacy           | 117.50                    |
| Switches              | 50000       |                         |                           |
| Beam angle            | 360 °       | LED                     |                           |
| Dimmable              | Yes         | Filament LED            | Yes                       |
| Degree of protection  | IP20        | LED type                | Ceramic                   |
| Net weight            | 0.022 kg    | Dimm type               | Trailing and leading edge |
| Warranty              | 2 years     | Number of leds / sticks | 4                         |
|                       |             | Stick length            | 38 mm                     |
|                       |             | Stick mounting          | Vertical                  |
|                       |             | Colour consistency SDCM | SDCM6                     |
|                       |             | Dim to warm             | No                        |
|                       |             | Adjustable beam angle   | No                        |
|                       |             | Ordering details        |                           |
|                       |             | L227250827-1            | Quantity pc(s)            |
|                       |             | Single package          | 1                         |
|                       |             | Inner carton            | 10                        |
|                       |             | Outer carton            | 60                        |

|                             |        |
|-----------------------------|--------|
| Light                       |        |
| Kelvin                      | 2700 K |
| Colour temp nr              | 827    |
| Stable lumen                | 470 lm |
| Color Rendering Index (CRI) | 82     |

|                |  |     |
|----------------|--|-----|
| Quantity pc(s) |  | EAN |
| 8718739066823  |  |     |
| 18718739066820 |  |     |
| 28718739066827 |  |     |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

08-09-2024