



L229355530

LED Ba22d Tube T27x58mm 100-240V
550Lm 4.5W 3000K 830 360° AC/DC
Helder Niet-Dimbaar

**Marine & Industrie, Tubular VR
100-240V Premium**



General

| | |
|----------------------|--------------|
| Epel registration no | 831356 |
| Socket | Ba22d |
| Bulb shape | T27 |
| Width | 27.00 mm |
| Depth | 27.00 mm |
| Height | 58.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Polycarbonat |
| Lifespan | 30000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.033 kg |
| Warranty | 3 years |

Light

| | |
|-----------------------------|--------|
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 550 lm |
| Color Rendering Index (CRI) | 82 |

Energy

| | |
|-------------------------|------------|
| Volt | 100..240 V |
| Frequency | 50..60 Hz |
| Watt | 4.5 W |
| Current type | AC/DC |
| Power factor | 0.5 |
| Energy efficiency class | E |
| Energy consumption | 5 W |
| Replacement wattage | 45 W |
| Lamp efficacy | 122.22 |

LED

| | |
|-------------------------|---------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Non-Dim |
| Number of leds / sticks | 54 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

Ordering details

| | | |
|----------------|----------------|----------------|
| L229355530 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739054011 |
| Inner carton | 10 | 18718739054018 |
| Outer carton | 100 | 28718739054015 |