



L276505501

LED E27 DimToWarm GLS A65x128mm
230V 1050Lm 14W 2000-2700K 920-927
270° AC Opaal Dimbaar

Huishoudelijk, Dim To Warm



| General | | Energy | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------------|---|------------|----------------|----------------|-----|----------------|----------|---------------|--------------|---------------------------|----------------|-------------------------|----|----------------|-------------------------|-------|--|-------------|-----|--|-----------------------|----|--|
| Eprel registration no | 831425 | Operating voltage | 230 V | | | | | | | | | | | | | | | | | | | | | |
| Socket | E27 | Volt | 220..240 V | | | | | | | | | | | | | | | | | | | | | |
| Bulb shape | A65 | Frequency | 50..60 Hz | | | | | | | | | | | | | | | | | | | | | |
| Width | 65.00 mm | Watt | 14 W | | | | | | | | | | | | | | | | | | | | | |
| Depth | 65.00 mm | Current type | AC | | | | | | | | | | | | | | | | | | | | | |
| Height | 128.00 mm | Power factor | 0.95 | | | | | | | | | | | | | | | | | | | | | |
| Finish | Opal | Energy efficiency class | G | | | | | | | | | | | | | | | | | | | | | |
| Colour | White | Energy consumption | 14 W | | | | | | | | | | | | | | | | | | | | | |
| Colour housing | White | Replacement wattage | 75 W | | | | | | | | | | | | | | | | | | | | | |
| Body material | Polycarbonat | Lamp efficacy | 75.00 | | | | | | | | | | | | | | | | | | | | | |
| Lifespan | 25000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 3628</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">40</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM6</td></tr><tr><td>Dim to warm</td><td colspan="2">Yes</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table> | | Filament LED | No | | LED type | SMD 3628 | | Dimm type | Trailing and leading edge | | Number of leds / sticks | 40 | | Colour consistency SDCM | SDCM6 | | Dim to warm | Yes | | Adjustable beam angle | No | |
| Filament LED | No | | | | | | | | | | | | | | | | | | | | | | | |
| LED type | SMD 3628 | | | | | | | | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 40 | | | | | | | | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | | | | | | | | |
| Dim to warm | Yes | | | | | | | | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | | | | | | | | |
| Switches | 50000 | | | | | | | | | | | | | | | | | | | | | | | |
| Beam angle | 270 ° | | | | | | | | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | | | | | | | | |
| Net weight | 0.112 kg | | | | | | | | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | | | | | | | | |
| Light | | <div>Ordering details</div> <table><tr><td>L276505501</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739049574</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739049571</td></tr><tr><td>Outer carton</td><td>60</td><td>28718739049578</td></tr></table> | | L276505501 | Quantity pc(s) | EAN | Single package | 1 | 8718739049574 | Inner carton | 10 | 18718739049571 | Outer carton | 60 | 28718739049578 | | | | | | | | | |
| L276505501 | Quantity pc(s) | | | EAN | | | | | | | | | | | | | | | | | | | | |
| Single package | 1 | | | 8718739049574 | | | | | | | | | | | | | | | | | | | | |
| Inner carton | 10 | | | 18718739049571 | | | | | | | | | | | | | | | | | | | | |
| Outer carton | 60 | 28718739049578 | | | | | | | | | | | | | | | | | | | | | | |
| Kelvin | 2200..2700 K | | | | | | | | | | | | | | | | | | | | | | | |
| Colour temp nr | 920..927 | | | | | | | | | | | | | | | | | | | | | | | |
| Stable lumen | 1050 lm | | | | | | | | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 97 | | | | | | | | | | | | | | | | | | | | | | | |
| Remark | | | | | | | | | | | | | | | | | | | | | | | | |
| Dimming levels: Step 1: 100% brightness; step 2: 50% brightness; step 3: 25% brightness. | | | | | | | | | | | | | | | | | | | | | | | | |

