



L490215830

LED G13 Glas T8 Tube T26x1514mm
including pin 230V 3700Lm 24W 3000K
830 210° AC Milky Niet-Dimbaar

Marine & Industrie, T8 Tube Premium



| General | | Energy | |
|-----------------------------|-------------|-------------------------|--------------------|
| Epel registration no | 831506 | Operating voltage | 230 V |
| Socket | G13 | Volt | 220..240 V |
| Bulb shape | T8 | Frequency | 50..60 Hz |
| Width | 1514.00 mm | Watt | 24 W |
| Depth | 26.00 mm | Current type | AC |
| Height | 26.00 mm | Power factor | 0.9 |
| Finish | Opal | Energy efficiency class | D |
| Colour | White | Energy consumption | 24 W |
| Colour housing | White | Replacement wattage | 197 W |
| Body material | Glass | Lamp efficacy | 154.17 |
| Lifespan | 50000 hours | LED | |
| Switches | 25000 | Filament LED | No |
| Beam angle | 210 ° | LED type | SMD 2835 |
| Dimmable | No | Dimm type | Non-Dim |
| Degree of protection | IP20 | Number of leds / sticks | 180 |
| Net weight | 0.242 kg | Colour consistency SDCM | SDCM5 |
| Warranty | 2 years | Dim to warm | No |
| Light | | Adjustable beam angle | No |
| Kelvin | 3000 K | Ordering details | |
| Colour temp nr | 830 | L490215830 | Quantity pc(s) EAN |
| Stable lumen | 3700 lm | Single package | 1 8718739061750 |
| Color Rendering Index (CRI) | 80 | Outer carton | 25 28718739061754 |

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).