



PROFESSIONAL
LIGHTING

L571210927

LED G53 AR111x67mm 12V 650Lm 12W
2700K 927 10° AC/DC Grijs Dimbaar

Specials & Projecten, Spot G53 AR111
Dimmable Premium



| General | | Energy | |
|-----------------------------|-------------|-------------------------|---------------------------|
| Epel registration no | 831526 | Operating voltage | 12 V |
| Socket | G53 | Volt | 10..14 V |
| Bulb shape | AR111 | Frequency | 50..60 Hz |
| Width | 111.00 mm | Watt | 12 W |
| Depth | 111.00 mm | Current type | AC/DC |
| Height | 67.00 mm | Power factor | 0.9 |
| Finish | Clear | Energy efficiency class | G |
| Colour | Silver | Energy consumption | 12 W |
| Colour housing | Grey | Lamp efficacy | 54.17 |
| Body material | Aluminium | LED | |
| Lifespan | 25000 hours | Filament LED | No |
| Switches | 30000 | LED type | COB |
| Beam angle | 10 ° | Dimm type | Trailing and leading edge |
| Dimmable | Yes | Number of leds / sticks | 1 |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM3 |
| Net weight | 0.098 kg | Dim to warm | No |
| Warranty | 3 years | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 2700 K | L571210927 | Quantity pc(s) EAN |
| Colour temp nr | 927 | Single package | 1 8718739063594 |
| Stable lumen | 690 lm | Inner carton | 10 18718739063591 |
| Lumen 90 cone | 650 lm | Outer carton | 50 28718739063598 |
| Luminous intensity | 7900 cd | | |
| Color Rendering Index (CRI) | 92 | | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

