



L642734527

LED GU5.3 MR16 Glas 50x45mm 12V 350Lm
2.7W 2700K 827 36° AC/DC Niet-Dimbaar

Huishoudelijk, Spot GU5.3 12V Glass



| General | | Energy | | | | | | | | | | | | | | | |
|-------------------------|-------------|--|-----------|--------------|----|----------|-----|-----------|---------|-------------------------|---|-------------------------|-------|-------------|----|-----------------------|----|
| Eprel registration no | 1379480 | Operating voltage | 12 V | | | | | | | | | | | | | | |
| Socket | GU5.3 | Volt | 12 V | | | | | | | | | | | | | | |
| Bulb shape | MR16 | Frequency | 50..60 Hz | | | | | | | | | | | | | | |
| Width | 50.00 mm | Watt | 2.7 W | | | | | | | | | | | | | | |
| Depth | 50.00 mm | Current type | AC/DC | | | | | | | | | | | | | | |
| Height | 45.00 mm | Power factor | 0.6 | | | | | | | | | | | | | | |
| Finish | Clear | Energy efficiency class | D | | | | | | | | | | | | | | |
| Colour | Colourless | Energy consumption | 3 W | | | | | | | | | | | | | | |
| Colour housing | Silver | Lamp efficacy | 129.63 | | | | | | | | | | | | | | |
| Body material | Glass | <div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td>9</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | No | LED type | SMD | Dimm type | Non-Dim | Number of leds / sticks | 9 | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | No | | | | | | | | | | | | | | | | |
| LED type | SMD | | | | | | | | | | | | | | | | |
| Dimm type | Non-Dim | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 9 | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | |
| Lifespan | 25000 hours | | | | | | | | | | | | | | | | |
| Switches | 50000 | | | | | | | | | | | | | | | | |
| Beam angle | 36 ° | | | | | | | | | | | | | | | | |
| Dimmable | No | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | |
| Net weight | 0.036 kg | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | |

| Light | | Ordering details | | |
|-----------------------------|--------|------------------|----------------|----------------|
| Kelvin | 2700 K | L642734527 | Quantity pc(s) | EAN |
| Colour temp nr | 827 | Single package | 1 | 8718739068384 |
| Stable lumen | 380 lm | Inner carton | 10 | 18718739068381 |
| Lumen 90 cone | 350 lm | Outer carton | 100 | 28718739068388 |
| Luminous intensity | 900 cd | | | |
| Color Rendering Index (CRI) | 80 | | | |

