



PROFESSIONAL  
LIGHTING

## L642742630

LED GU5.3 MR16 50x48mm 24-30V 425Lm  
6W 3000K 830 38° DC Niet-Dimbaar

**Marine & Industrie, Spot GU5.3 24V  
Premium**



| General                     |              | Energy                  |                |                |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no       | 831583       | Volt                    | 24..30 V       |                |
| Socket                      | GU5.3        | Frequency               | 50 Hz          |                |
| Bulb shape                  | MR16         | Watt                    | 6 W            |                |
| Width                       | 50.00 mm     | Current type            | DC             |                |
| Depth                       | 50.00 mm     | Power factor            | 1              |                |
| Height                      | 48.00 mm     | Energy efficiency class | G              |                |
| Finish                      | Clear        | Energy consumption      | 6 W            |                |
| Colour                      | Colourless   | Lamp efficacy           | 70.83          |                |
| Colour housing              | White        |                         |                |                |
| Body material               | Polycarbonat | LED                     |                |                |
| Lifespan                    | 15000 hours  | Filament LED            | No             |                |
| Switches                    | 50000        | LED type                | SMD 2835       |                |
| Beam angle                  | 38 °         | Dimm type               | Non-Dim        |                |
| Dimmable                    | No           | Number of leds / sticks | 8              |                |
| Degree of protection        | IP20         | Colour consistency SDCM | SDCM5          |                |
| Net weight                  | 0.026 kg     | Dim to warm             | No             |                |
| Warranty                    | 3 years      | Adjustable beam angle   | No             |                |
|                             |              | Ordering details        |                |                |
| Light                       |              | L642742630              | Quantity pc(s) | EAN            |
| Kelvin                      | 3000 K       | Single package          | 1              | 8718739057579  |
| Colour temp nr              | 830          | Inner carton            | 10             | 18718739057576 |
| Stable lumen                | 475 lm       | Outer carton            | 100            | 28718739057573 |
| Lumen 90 cone               | 425 lm       |                         |                |                |
| Luminous intensity          | 650 cd       |                         |                |                |
| Color Rendering Index (CRI) | 82           |                         |                |                |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

