



PROFESSIONAL  
LIGHTING

## L643090065

LED GU10 Glas 30x80mm 230V 440Lm 4W  
6500K 865 AC Niet-Dimbaar

Huishoudelijk, GU10 Glass



General		Energy																							
Eprel registration no	695078	Operating voltage		230 V																					
Socket	GU10	Volt		220..240 V																					
Bulb shape	T30	Frequency		50..60 Hz																					
Width	30.00 mm	Watt		4 W																					
Depth	30.00 mm	Current type		AC																					
Height	80.00 mm	Power factor		0.5																					
Finish	Clear	Energy efficiency class		E																					
Colour	Colourless	Energy consumption		4 W																					
Colour housing	White	Replacement wattage		38 W																					
Body material	Glass	Lamp efficacy		110.00																					
Lifespan	20000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD</td></tr><tr><td>Dimm type</td><td colspan="2">Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">34</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD		Dimm type	Non-Dim		Number of leds / sticks	34		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD																								
Dimm type	Non-Dim																								
Number of leds / sticks	34																								
Colour consistency SDCM	SDCM5																								
Dim to warm	No																								
Adjustable beam angle	No																								
Switches	10000																								
Beam angle	300 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.027 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	6300..6600 K	L643090065	Quantity pc(s)	EAN																					
Colour temp nr	865	Single package	1	8718739065000																					
Stable lumen	440 lm	Inner carton	10	18718739065007																					
Color Rendering Index (CRI)	80	Outer carton	200	28718739065004																					



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

21-11-2024