



L651441327

LED E27 UFO R145x75mm 230V
1350Lm(120° Flux 950Lm) 15W 2700K 827
120° AC Dimbaar



Huishoudelijk, Ufo

General		Energy															
Eprel registration no	1550607	Operating voltage	230 V														
Socket	E27	Volt	220..240 V														
Width	145.00 mm	Frequency	50..60 Hz														
Depth	145.00 mm	Watt	15 W														
Height	75.00 mm	Current type	AC														
Finish	Translucent	Power factor	0.5														
Colour	White	Energy efficiency class	F														
Colour housing	White	Energy consumption	15 W														
Body material	Polycarbonat	Lamp efficacy	90.00														
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>30</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	No	LED type	SMD	Dimm type	Trailing and leading edge	Number of leds / sticks	30	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	No																
LED type	SMD																
Dimm type	Trailing and leading edge																
Number of leds / sticks	30																
Colour consistency SDCM	SDCM6																
Dim to warm	No																
Adjustable beam angle	No																
Switches	12500																
Beam angle	120 °																
Dimmable	Yes																
Degree of protection	IP20																
Net weight	0.110 kg																
Warranty	2 years																
Light		<div>Ordering details</div> <table><tr><td>L651441327</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739070110</td></tr><tr><td>Outer carton</td><td>10</td><td>28718739070114</td></tr></table>		L651441327	Quantity pc(s)	EAN	Single package	1	8718739070110	Outer carton	10	28718739070114					
L651441327	Quantity pc(s)			EAN													
Single package	1			8718739070110													
Outer carton	10			28718739070114													
Kelvin	2700 K																
Colour temp nr	827																
Stable lumen	1350 lm																
Lumen 90 cone	650 lm																
Lumen 120 cone	950 lm																
Luminous intensity	405 cd																
Color Rendering Index (CRI)	80																

