



PROFESSIONAL
LIGHTING

LF023810301

LED E14 Filament Kaars Gedraaid
C35x100mm 230V 320Lm 4W 2500K 925
360° AC Mat Dimbaar

Decoratief, Twisted Candle Premium



General		Energy	
Epel registration no	545618	Operating voltage	230 V
Socket	E14	Volt	220..240 V
Bulb shape	C35	Frequency	50..60 Hz
Width	35.00 mm	Watt	4 W
Depth	35.00 mm	Current type	AC
Height	100.00 mm	Power factor	0.9
Finish	Frosted	Energy efficiency class	G
Colour	Colourless	Energy consumption	4 W
Body material	Glass	Replacement wattage	30 W
Lifespan	25000 hours	Lamp efficacy	80.00
Switches	50000	LED	
Beam angle	360 °	Filament LED	Yes
Dimmable	Yes	LED type	Sapphire
Degree of protection	IP20	Dimm type	Trailing and leading edge
Net weight	0.014 kg	Number of leds / sticks	4
Warranty	2 years	Stick length	38 mm
Light		Stick mounting	Twisted
Kelvin	2500 K	Colour consistency SDCM	SDCM6
Colour temp nr	925	Dim to warm	No
Stable lumen	320 lm	Adjustable beam angle	No
Color Rendering Index (CRI)	95	Ordering details	
		LF023810301	Quantity pc(s)
		Single package	1
		Inner carton	10
		Outer carton	100
		EAN	
		8718739055889	
		18718739055886	
		28718739055883	



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)