



PROFESSIONAL
LIGHTING

LF023825401

LED E27 Fila Laser Stripe G125x180mm
230V 120Lm 4W 2500K 925 360° AC Zwart
Zilver Dimbaar

Decoratief, Globe G125 Laser Premium



General		Energy																			
Epel registration no	1060269	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	G125	Frequency	50..60 Hz																		
Width	125.00 mm	Watt	4 W																		
Depth	125.00 mm	Current type	AC																		
Height	180.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	G																		
Colour	Black Silver	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	13 W																		
Lifespan	15000 hours	Lamp efficacy	30.00																		
Switches	30000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Twisted - Top narrow bottom wide	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Twisted - Top narrow bottom wide																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.092 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	2500 K	LF023825401	Quantity pc(s)																		
Colour temp nr	925	Single package	1																		
Stable lumen	120 lm	Outer carton	12																		
Color Rendering Index (CRI)	90		EAN																		
			8718739064126																		
			28718739064120																		



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

22-11-2024