



LF023841505-1

LED E14 Filament Kaars C35x100mm 230V
100Lm 2W 2200K 922 360° AC Goud
Dimbaar

Decoratief, Candle Premium



General		Energy																			
Epel registration no	765758	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	C35	Frequency	50..60 Hz																		
Width	35.00 mm	Watt	2 W																		
Depth	35.00 mm	Current type	AC																		
Height	100.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	2 W																		
Body material	Glass	Replacement wattage	11 W																		
Lifespan	25000 hours	Lamp efficacy	50.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>2</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	2	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	2																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LF023841505-1</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739065376</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739065373</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739065370</td></tr></table>		LF023841505-1	Quantity pc(s)	EAN	Single package	1	8718739065376	Inner carton	10	18718739065373	Outer carton	100	28718739065370						
LF023841505-1	Quantity pc(s)			EAN																	
Single package	1			8718739065376																	
Inner carton	10			18718739065373																	
Outer carton	100			28718739065370																	
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	100 lm																				
Color Rendering Index (CRI)	93																				

