



PROFESSIONAL  
LIGHTING

## LX023811509

LED E14 Filament Kaars Gedraaid  
C35x100mm 230V 120Lm 2W 2200K 922  
360° AC Helder Dimbaar

## Decoratief, Twisted Candle Premium



General		Energy	
Epel registration no	1441230	Operating voltage	230 V
Socket	E14	Volt	220..240 V
Bulb shape	C35	Frequency	50..60 Hz
Width	35.00 mm	Watt	2 W
Depth	35.00 mm	Current type	AC
Height	100.00 mm	Power factor	0.85
Finish	Clear	Energy efficiency class	G
Colour	Colourless	Energy consumption	2 W
Body material	Glass	Replacement wattage	13 W
Lifespan	25000 hours	Lamp efficacy	60.00
Switches	15000	LED	
Beam angle	360 °	Filament LED	Yes
Dimmable	Yes	LED type	Ceramic
Degree of protection	IP20	Dimm type	Trailing and leading edge
Net weight	0.015 kg	Number of leds / sticks	2
Warranty	2 years	Stick length	38 mm
Light		Stick mounting	Vertical
Kelvin	2200 K	Colour consistency SDCM	SDCM6
Colour temp nr	922	Dim to warm	No
Stable lumen	120 lm	Adjustable beam angle	No
Color Rendering Index (CRI)	93	Ordering details	
		LX023811509	Quantity pc(s) EAN
		Single package	1 8718739068919
		Inner carton	10 18718739068916
		Outer carton	100 28718739068913



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)