



PROFESSIONAL  
LIGHTING

## LX023822505

LED E27 Filament Tube T45x130mm 230V  
550Lm 6.5W 2200K 922 360° AC Goud  
Dimbaar

## Decoratief, Tubular Deco Premium



General		Energy																			
Epel registration no	1318259	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	T45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	6.5 W																		
Depth	45.00 mm	Current type	AC																		
Height	130.00 mm	Power factor	0.85																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	7 W																		
Body material	Glass	Replacement wattage	45 W																		
Lifespan	25000 hours	Lamp efficacy	84.62																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>68 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	6	Stick length	68 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	6																				
Stick length	68 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.046 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023822505</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739067660</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739067667</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739067664</td></tr></table>		LX023822505	Quantity pc(s)	EAN	Single package	1	8718739067660	Inner carton	10	18718739067667	Outer carton	100	28718739067664						
LX023822505	Quantity pc(s)			EAN																	
Single package	1			8718739067660																	
Inner carton	10			18718739067667																	
Outer carton	100			28718739067664																	
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	550 lm																				
Color Rendering Index (CRI)	90																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)