



PROFESSIONAL
LIGHTING

LX023833302

LED E27 Filament Tube T45x130mm 230V
600Lm 6.5W 2500K 925 360° AC Helder
Dimbaar

Decoratief, Tubular Deco Premium



General		Energy																			
Eprel registration no	1523663	Operating voltage	230 V																		
Socket	E27	Volt	220..240 V																		
Bulb shape	T45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	6.5 W																		
Depth	45.00 mm	Current type	AC																		
Height	130.00 mm	Power factor	0.8																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	7 W																		
Body material	Glass	Replacement wattage	48 W																		
Lifespan	25000 hours	Lamp efficacy	92.31																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>6</td></tr><tr><td>Stick length</td><td>68 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	6	Stick length	68 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	6																				
Stick length	68 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.035 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>LX023833302</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739069657</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739069654</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739069651</td></tr></table>		LX023833302	Quantity pc(s)	EAN	Single package	1	8718739069657	Inner carton	10	18718739069654	Outer carton	100	28718739069651						
LX023833302	Quantity pc(s)			EAN																	
Single package	1			8718739069657																	
Inner carton	10			18718739069654																	
Outer carton	100			28718739069651																	
Kelvin	2500 K																				
Colour temp nr	925																				
Stable lumen	600 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

05-07-2024