



PROFESSIONAL
LIGHTING

LX023840308

LED E14 Filament Kaars C35x97mm 230V
250Lm 3W 2500K 925 360° AC Opaal
Dimbaar

Decoratief, Candle Premium



General		Energy	
Epel registration no	1318260	Operating voltage	230 V
Socket	E14	Volt	185..265 V
Bulb shape	C35	Frequency	50..60 Hz
Width	35.00 mm	Watt	3 W
Depth	35.00 mm	Current type	AC
Height	97.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	G
Colour	White	Energy consumption	3 W
Body material	Glass	Replacement wattage	25 W
Lifespan	25000 hours	Lamp efficacy	83.33
Switches	30000	LED	
Beam angle	360 °	Filament LED	Yes
Dimmable	Yes	LED type	Ceramic
Degree of protection	IP20	Dimm type	Trailing and leading edge
Net weight	0.014 kg	Number of leds / sticks	4
Warranty	2 years	Stick length	38 mm
Light		Stick mounting	Twisted
Kelvin	2500 K	Colour consistency SDCM	SDCM6
Colour temp nr	925	Dim to warm	No
Stable lumen	250 lm	Adjustable beam angle	No
Color Rendering Index (CRI)	90	Ordering details	
		LX023840308	Quantity pc(s) EAN
		Single package	1 8718739067707
		Inner carton	10 18718739067704
		Outer carton	100 28718739067701



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

05-10-2024