



PROFESSIONAL
LIGHTING

LX023851509

LED E14 Filament Tip Kaars C35x120mm
230V 140Lm 1.5W 2200K 922 360° AC
Helder Dimbaar

Decoratief, Tip Candle Premium



| General | |
|----------------------|-------------|
| Epel registration no | 1586674 |
| Socket | E14 |
| Bulb shape | C35 |
| Width | 35.00 mm |
| Depth | 35.00 mm |
| Height | 120.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.015 kg |
| Warranty | 2 years |

Light

| | |
|-----------------------------|--------|
| Kelvin | 2200 K |
| Colour temp nr | 922 |
| Stable lumen | 140 lm |
| Color Rendering Index (CRI) | 93 |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 1.5 W |
| Current type | AC |
| Power factor | 0.95 |
| Energy efficiency class | F |
| Energy consumption | 2 W |
| Replacement wattage | 15 W |
| Lamp efficacy | 93.33 |

LED

| | |
|-------------------------|---------------------------|
| Filament LED | Yes |
| LED type | Ceramic |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 2 |
| Stick length | 38 mm |
| Stick mounting | Vertical |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

Ordering details

| | | |
|----------------|----------------|----------------|
| LX023851509 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739068995 |
| Inner carton | 10 | 18718739068992 |
| Outer carton | 100 | 28718739068999 |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)