



PROFESSIONAL
LIGHTING

LX272532927

LED E27 Filament Globe G125x180mm 230V
450Lm 4.5W 2700K 827 360° AC Helder
Dimbaar

Decoratief, Globe G125



| General | | Energy | | | | | | | | | | | | | | | | | | | |
|-----------------------------|---------------------------|--|-----------------------|--------------|-----|----------|---------|-----------|---------------------------|-------------------------|---|--------------|-------|----------------|----------|-------------------------|-------|-------------|----|-----------------------|----|
| Epel registration no | 1420791 | Operating voltage | 230 V | | | | | | | | | | | | | | | | | | |
| Socket | E27 | Volt | 220..240 V | | | | | | | | | | | | | | | | | | |
| Bulb shape | G125 | Frequency | 50..60 Hz | | | | | | | | | | | | | | | | | | |
| Width | 125.00 mm | Watt | 4.5 W | | | | | | | | | | | | | | | | | | |
| Depth | 125.00 mm | Current type | AC | | | | | | | | | | | | | | | | | | |
| Height | 180.00 mm | Power factor | 0.8 | | | | | | | | | | | | | | | | | | |
| Finish | Clear | Energy efficiency class | F | | | | | | | | | | | | | | | | | | |
| Colour | Colourless | Energy consumption | 5 W | | | | | | | | | | | | | | | | | | |
| Body material | Glass | Replacement wattage | 39 W | | | | | | | | | | | | | | | | | | |
| Lifespan | 15000 hours | Lamp efficacy | 100.00 | | | | | | | | | | | | | | | | | | |
| Switches | 50000 | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | Yes | LED type | Ceramic | Dimm type | Trailing and leading edge | Number of leds / sticks | 4 | Stick length | 38 mm | Stick mounting | Straight | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | Yes | | | | | | | | | | | | | | | | | | | | |
| LED type | Ceramic | | | | | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 4 | | | | | | | | | | | | | | | | | | | | |
| Stick length | 38 mm | | | | | | | | | | | | | | | | | | | | |
| Stick mounting | Straight | | | | | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | | | | | |
| Beam angle | 360 ° | | | | | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | | | | | |
| Net weight | 0.092 kg | | | | | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | | | | | |
| Kelvin | 2700 K | LX272532927 | Quantity pc(s) EAN | | | | | | | | | | | | | | | | | | |
| Colour temp nr | 827 | Single package | 1 8718739068612 | | | | | | | | | | | | | | | | | | |
| Stable lumen | 450 lm | Outer carton | 12 28718739068616 | | | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 82 | | | | | | | | | | | | | | | | | | | | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

05-07-2024