



PROFESSIONAL  
LIGHTING

### L021136027-1

LED GU4 MR11 Glass 35x38mm 12V 345Lm  
4.4W 2700K 827 36° AC/DC Dimmable

Household, Spot GU4 12V Dimmable



General		Energy															
Eprel registration no	1232174	Operating voltage	12 V														
Socket	GU4	Volt	12 V														
Bulb shape	MR11	Frequency	50..60 Hz														
Width	35.00 mm	Watt	4.4 W														
Depth	35.00 mm	Current type	AC/DC														
Height	38.00 mm	Power factor	0.9														
Finish	Clear	Energy efficiency class	F														
Colour	Colourless	Energy consumption	4 W														
Colour housing	Silver	Lamp efficacy	78.41														
Body material	Glass	<div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD 2835</td></tr><tr><td>Dimm type</td><td>Trailing edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	No	LED type	SMD 2835	Dimm type	Trailing edge	Number of leds / sticks	4	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	No																
LED type	SMD 2835																
Dimm type	Trailing edge																
Number of leds / sticks	4																
Colour consistency SDCM	SDCM6																
Dim to warm	No																
Adjustable beam angle	No																
Lifespan	25000 hours																
Switches	50000																
Beam angle	36 °																
Dimmable	Yes																
Degree of protection	IP20																
Net weight	0.020 kg																
Warranty	2 years																
Light		Ordering details															
Kelvin	2700 K	L021136027-1	Quantity pc(s) EAN														
Colour temp nr	827	Single package	1 8718739067073														
Stable lumen	400 lm	Inner carton	10 18718739067070														
Lumen 90 cone	345 lm	Outer carton	100 28718739067077														
Luminous intensity	600 cd																
Color Rendering Index (CRI)	82																



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

11-03-2025