

L021136027-2

LED GU4 MR11 Glass 35x38mm 12V 350Lm
4.2W 2700K 827 36° AC/DC Dimmable

Household, Spot GU4 12V



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 2404850 | Operating voltage | 12 V | |
| Socket | GU4 | Volt | 12 V | |
| Bulb shape | MR11 | Frequency | 50..60 Hz | |
| Width | 35.00 mm | Watt | 4.2 W | |
| Depth | 35.00 mm | Current type | AC/DC | |
| Height | 38.00 mm | Power factor | 0.94 | |
| Finish | Clear | Energy efficiency class | F | |
| Colour | Colourless | Energy consumption | 4 W | |
| Colour housing | Colourless | Lamp efficacy | 83.33 | |
| Body material | Glass | LED | | |
| Lifespan | 25000 hours | Filament LED | No | |
| Switches | 50000 | LED type | SMD 2835 | |
| Beam angle | 36 ° | Dimm type | Trailing edge | |
| Dimmable | Yes | Number of leds / sticks | 4 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.020 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 2700 K | L021136027-2 | Quantity pc(s) | EAN |
| Colour temp nr | 827 | Single package | 1 | 8718739082816 |
| Stable lumen | 400 lm | Inner carton | 10 | 18718739082813 |
| Lumen 90 cone | 350 lm | Outer carton | 100 | 28718739082810 |
| Luminous intensity | 566 cd | | | |
| Color Rendering Index (CRI) | 82 | | | |