



L021222040-1

LED G12 T30x110mm 230V 2100Lm 18W
4000K 840 360° AC Clear Dimmable

Specials & Projects, G12 230V Premium



| General | | Energy | | | | | | | | | | | | | | | |
|---|---------------------------|---|----------------|----------------|----|----------|----------|-----------|---------------------------|-------------------------|-----|-------------------------|-------|-------------|----|-----------------------|----|
| Eprel registration no | 2271204 | Operating voltage | 230 V | | | | | | | | | | | | | | |
| Socket | G12 | Volt | 220..240 V | | | | | | | | | | | | | | |
| Bulb shape | T30 | Frequency | 50..60 Hz | | | | | | | | | | | | | | |
| Width | 30.00 mm | Watt | 18 W | | | | | | | | | | | | | | |
| Depth | 30.00 mm | Current type | AC | | | | | | | | | | | | | | |
| Height | 110.00 mm | Power factor | 0.5 | | | | | | | | | | | | | | |
| Finish | Clear | Energy efficiency class | E | | | | | | | | | | | | | | |
| Colour | Colourless | Energy consumption | 18 W | | | | | | | | | | | | | | |
| Body material | Aluminium | Replacement wattage | 131 W | | | | | | | | | | | | | | |
| Lifespan | 25000 hours | Lamp efficacy | 116.67 | | | | | | | | | | | | | | |
| Switches | 15000 | <div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD 2835</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>120</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | No | LED type | SMD 2835 | Dimm type | Trailing and leading edge | Number of leds / sticks | 120 | Colour consistency SDCM | SDCM5 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | No | | | | | | | | | | | | | | | | |
| LED type | SMD 2835 | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 120 | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM5 | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | |
| Beam angle | 360 ° | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | |
| Net weight | 0.048 kg | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | |
| Kelvin | 4000 K | L021222040-1 | Quantity pc(s) | EAN | | | | | | | | | | | | | |
| Colour temp nr | 840 | Single package | 1 | 8718739081147 | | | | | | | | | | | | | |
| Stable lumen | 2100 lm | Inner carton | 10 | 18718739081144 | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739081141 | | | | | | | | | | | | | |
| Remark | | | | | | | | | | | | | | | | | |
| Replace existing lamps with these 230V mains-powered LED's by removing the ballast and connecting the lamp holder on 230V mains | | | | | | | | | | | | | | | | | |