PROFESSIONAL LIGHTING

L021222040-1

LED G12 T30x110mm 230V 2100Lm 18W
4000K 840 360° AC Clear Dimmable

Specials & Projects, G12 230V Premium





General	
Eprel registration no	2271204
Socket	G12
Bulb shape	T30
Width	30.00 mm
Depth	30.00 mm
Height	110.00 mm
Finish	Clear
Colour	Colourless
Body material	Aluminium
Lifespan	25000 hours
Switches	15000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.093 kg
Warranty	2 years

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	2100 lm

Remark
Replace existing lamps with these 230V mains-powered LED's by removing the ballast and connecting the lamp holder on 230V mains Warranty void if used in enclosed luminaires

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	18 W
Current type	AC
Power factor	0.5
Energy efficiency class	E
Energy consumption	18 W
Lamp efficacy	116.67

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Trailing and leading edge
Number of leds / sticks	120
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details		
L021222040-1	Quantity pc(s)	EAN
Single package	1	8718739081147
Inner carton	10	18718739081144
Outer carton	100	28718739081141

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal