

L022171827-1

LED G9 T17x50mm 230V 260Lm 3W 2700K
827 360° AC Clear Dimmable

Household, G9



General		Energy																							
Eprel registration no	1427455	Operating voltage	230 V																						
Socket	G9	Volt	220..240 V																						
Bulb shape	T17	Frequency	50..60 Hz																						
Width	17.00 mm	Watt	3 W																						
Depth	17.00 mm	Current type	AC																						
Height	50.00 mm	Power factor	0.9																						
Finish	Clear	Energy efficiency class	F																						
Colour	Colourless	Energy consumption	3 W																						
Body material	Polycarbonat	Replacement wattage	26 W																						
Lifespan	25000 hours	Lamp efficacy	86.67																						
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Triac</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">32</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM6</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD 2835		Dimm type	Triac		Number of leds / sticks	32		Colour consistency SDCM	SDCM6		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD 2835																								
Dimm type	Triac																								
Number of leds / sticks	32																								
Colour consistency SDCM	SDCM6																								
Dim to warm	No																								
Adjustable beam angle	No																								
Beam angle	360 °																								
Dimmable	Yes																								
Degree of protection	IP20																								
Net weight	0.010 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	2700 K	L022171827-1	Quantity pc(s)	EAN																					
Colour temp nr	827	Single package	1	8718739068964																					
Stable lumen	260 lm	Inner carton	10	18718739068961																					
Color Rendering Index (CRI)	80	Outer carton	100	28718739068968																					