



L022180805-1

LED G9 Fila T18x66mm 230V 240Lm 3W
2200K 922 360° AC Gold Dimmable

Household, G9 Fila Premium



General		Energy																			
Eprel registration no	1995035	Operating voltage	230 V																		
Socket	G9	Volt	220..240 V																		
Bulb shape	T18	Frequency	50..60 Hz																		
Width	18.00 mm	Watt	3 W																		
Depth	18.00 mm	Current type	AC																		
Height	66.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	G																		
Colour	Gold	Energy consumption	3 W																		
Colour housing	White	Replacement wattage	24 W																		
Body material	Ceramic	Lamp efficacy	80.00																		
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>26 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	26 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	26 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.009 kg																				
Warranty	3 years																				
Light		<div>Ordering details</div> <table><tr><td>L022180805-1</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739075092</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739075099</td></tr><tr><td>Outer carton</td><td>120</td><td>28718739075096</td></tr></table>		L022180805-1	Quantity pc(s)	EAN	Single package	1	8718739075092	Inner carton	10	18718739075099	Outer carton	120	28718739075096						
L022180805-1	Quantity pc(s)			EAN																	
Single package	1			8718739075092																	
Inner carton	10			18718739075099																	
Outer carton	120			28718739075096																	
Kelvin	2200 K																				
Colour temp nr	922																				
Stable lumen	240 lm																				
Color Rendering Index (CRI)	90																				

