



PROFESSIONAL
LIGHTING

L022336000

LED G9 DimToWarm T18x49mm 230V
360Lm 4W 2200-3000K 822-830 360° AC
Clear Dimmable

Household, Dim To Warm Premium



| General | | Energy | |
|-----------------------------|--------------|-------------------------|---------------------------|
| Eprel registration no | 1368338 | Operating voltage | 230 V |
| Socket | G9 | Volt | 220..240 V |
| Bulb shape | T18 | Frequency | 50..60 Hz |
| Width | 18.00 mm | Watt | 4 W |
| Depth | 18.00 mm | Current type | AC |
| Height | 49.00 mm | Power factor | 0.8 |
| Finish | Clear | Energy efficiency class | F |
| Colour | Colourless | Energy consumption | 4 W |
| Colour housing | Colourless | Replacement wattage | 33 W |
| Body material | Ceramic | Lamp efficacy | 90.00 |
| Lifespan | 25000 hours | | |
| Switches | 50000 | LED | |
| Beam angle | 360 ° | Filament LED | No |
| Dimmable | Yes | LED type | SMD |
| Degree of protection | IP20 | Dimm type | Trailing and leading edge |
| Net weight | 0.012 kg | Number of leds / sticks | 34 |
| Warranty | 3 years | Colour consistency SDCM | SDCM6 |
| | | Dim to warm | Yes |
| | | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 2200..3000 K | L022336000 | Quantity pc(s) |
| Colour temp nr | 822..830 | | EAN |
| Stable lumen | 360 lm | Single package | 1 |
| Color Rendering Index (CRI) | 80 | Inner carton | 10 |
| | | Outer carton | 100 |
| | | | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

03-12-2024