



PROFESSIONAL  
LIGHTING

L022453027

LED G4 T10x34mm 10-28V 100Lm 1W  
2700K 827 360° DC Dimmable

Marine & Industry, G4 VR 10-30V  
Premium



#### General

Epel registration no	728290
Socket	G4
Bulb shape	T10
Width	10.50 mm
Depth	10.50 mm
Height	34.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.004 kg
Warranty	3 years

#### Light

Kelvin	2700 K
Colour temp nr	827
Stable lumen	100 lm
Color Rendering Index (CRI)	82

#### Remark

Can withstand peak voltages until 30V - constant current can be 28V.

#### Energy

Operating voltage	12 V
Volt	10..28 V
Frequency	50 Hz
Watt	1 W
Current type	DC
Power factor	1
Energy efficiency class	F
Energy consumption	1 W
Replacement wattage	11 W
Lamp efficacy	100.00

#### LED

Filament LED	No
LED type	SMD 2835
Dimm type	Trailing and leading edge
Number of leds / sticks	11
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

#### Ordering details

L022453027	Quantity pc(s)	EAN
Single package	1	8718739061354
Inner carton	10	18718739061351
Outer carton	100	28718739061358



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



28-04-2025