



PROFESSIONAL  
LIGHTING

**L024070507**

LED Ba22d Filament GLS A60x105mm 230V  
470Lm 5.5W 2700K 927 360° AC Clear  
Dimmable

**Decorative, General Ba22d Premium**



| General                     |             | Energy                  |                                   |
|-----------------------------|-------------|-------------------------|-----------------------------------|
| Epel registration no        | 831211      | Operating voltage       | 230 V                             |
| Socket                      | Ba22d       | Volt                    | 220..240 V                        |
| Bulb shape                  | A60         | Frequency               | 50..60 Hz                         |
| Width                       | 60.00 mm    | Watt                    | 5.5 W                             |
| Depth                       | 60.00 mm    | Current type            | AC                                |
| Height                      | 105.00 mm   | Power factor            | 0.9                               |
| Finish                      | Clear       | Energy efficiency class | F                                 |
| Colour                      | Colourless  | Energy consumption      | 6 W                               |
| Body material               | Glass       | Replacement wattage     | 40 W                              |
| Lifespan                    | 25000 hours | Lamp efficacy           | 85.45                             |
| Switches                    | 50000       | LED                     |                                   |
| Beam angle                  | 360 °       | Filament LED            | Yes                               |
| Dimmable                    | Yes         | LED type                | Sapphire                          |
| Degree of protection        | IP20        | Dimm type               | Trailing and leading edge         |
| Net weight                  | 0.036 kg    | Number of leds / sticks | 6                                 |
| Warranty                    | 2 years     | Stick length            | 38 mm                             |
| Light                       |             | Stick mounting          | Straight - Top narrow bottom wide |
| Kelvin                      | 2700 K      | Colour consistency SDCM | SDCM6                             |
| Colour temp nr              | 927         | Dim to warm             | No                                |
| Stable lumen                | 470 lm      | Adjustable beam angle   | No                                |
| Color Rendering Index (CRI) | 93          | Ordering details        |                                   |
|                             |             | L024070507              | Quantity pc(s)                    |
|                             |             | Single package          | 1                                 |
|                             |             | Inner carton            | 10                                |
|                             |             | Outer carton            | 100                               |
|                             |             | EAN                     |                                   |
|                             |             | 8718739047662           |                                   |
|                             |             | 18718739047669          |                                   |
|                             |             | 28718739047666          |                                   |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

22-12-2024