



PROFESSIONAL
LIGHTING

L024070607

LED Ba22d Filament GLS A60x105mm 230V
540Lm 6.5W 2700K 927 360° AC Clear
Dimmable

Decorative, General Ba22d Premium



General		Energy																			
Epel registration no	831218	Operating voltage	230 V																		
Socket	Ba22d	Volt	220..240 V																		
Bulb shape	A60	Frequency	50..60 Hz																		
Width	60.00 mm	Watt	6.5 W																		
Depth	60.00 mm	Current type	AC																		
Height	105.00 mm	Power factor	0.9																		
Finish	Clear	Energy efficiency class	G																		
Colour	Colourless	Energy consumption	7 W																		
Body material	Glass	Replacement wattage	44 W																		
Lifespan	25000 hours	Lamp efficacy	83.08																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Sapphire</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>8</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight - Top narrow bottom wide</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Sapphire	Dimm type	Trailing and leading edge	Number of leds / sticks	8	Stick length	38 mm	Stick mounting	Straight - Top narrow bottom wide	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Sapphire																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	8																				
Stick length	38 mm																				
Stick mounting	Straight - Top narrow bottom wide																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.037 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L024070607</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739048164</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739048161</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739048168</td></tr></table>		L024070607	Quantity pc(s)	EAN	Single package	1	8718739048164	Inner carton	10	18718739048161	Outer carton	100	28718739048168						
L024070607	Quantity pc(s)			EAN																	
Single package	1			8718739048164																	
Inner carton	10			18718739048161																	
Outer carton	100			28718739048168																	
Kelvin	2700 K																				
Colour temp nr	927																				
Stable lumen	540 lm																				
Color Rendering Index (CRI)	93																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



23-12-2024