



PROFESSIONAL
LIGHTING

L024070607

LED Ba22d Filament GLS A60x105mm 230V
540Lm 6.5W 2700K 927 360° AC Clear
Dimmable

Decorative, General Ba22d Premium



| General | | Energy | |
|----------------------|-------------|-------------------------|-----------------------------------|
| Epel registration no | 831218 | Operating voltage | 230 V |
| Socket | Ba22d | Volt | 220..240 V |
| Bulb shape | A60 | Frequency | 50..60 Hz |
| Width | 60.00 mm | Watt | 6.5 W |
| Depth | 60.00 mm | Current type | AC |
| Height | 105.00 mm | Power factor | 0.9 |
| Finish | Clear | Energy efficiency class | G |
| Colour | Colourless | Energy consumption | 7 W |
| Body material | Glass | Replacement wattage | 44 W |
| Lifespan | 25000 hours | Lamp efficacy | 83.08 |
| Switches | 50000 | | |
| Beam angle | 360 ° | | |
| Dimmable | Yes | | |
| Degree of protection | IP20 | | |
| Net weight | 0.037 kg | | |
| Warranty | 2 years | | |
| | | | |
| LED | | | |
| | | Filament LED | Yes |
| | | LED type | Sapphire |
| | | Dimm type | Trailing and leading edge |
| | | Number of leds / sticks | 8 |
| | | Stick length | 38 mm |
| | | Stick mounting | Straight - Top narrow bottom wide |
| | | Colour consistency SDCM | SDCM6 |
| | | Dim to warm | No |
| | | Adjustable beam angle | No |
| Ordering details | | | |
| | | L024070607 | Quantity pc(s) |
| | | Single package | 1 |
| | | Inner carton | 10 |
| | | Outer carton | 100 |

| Light | |
|-----------------------------|--------|
| Kelvin | 2700 K |
| Colour temp nr | 927 |
| Stable lumen | 540 lm |
| Color Rendering Index (CRI) | 93 |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



23-11-2024