



PROFESSIONAL
LIGHTING

L024362430

LED E14 Tube T17x52mm 10-30V 180Lm
2W 3000K 830 360° AC/DC Clear Non-
Dimmable

**Marine & Industry, Tubular VR 10-30V
Premium**



General		Energy																							
Epel registration no	1233017	Volt	10..30 V																						
Socket	E14	Frequency	50..60 Hz																						
Bulb shape	T17	Watt	2 W																						
Width	17.00 mm	Current type	AC/DC																						
Depth	17.00 mm	Power factor	0.5																						
Height	52.00 mm	Energy efficiency class	G																						
Finish	Clear	Energy consumption	2 W																						
Colour	Colourless	Replacement wattage	19 W																						
Body material	Polycarbonat	Lamp efficacy	90.00																						
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD</td></tr><tr><td>Dimm type</td><td colspan="2">Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">13</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD		Dimm type	Non-Dim		Number of leds / sticks	13		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD																								
Dimm type	Non-Dim																								
Number of leds / sticks	13																								
Colour consistency SDCM	SDCM5																								
Dim to warm	No																								
Adjustable beam angle	No																								
Switches	50000																								
Beam angle	360 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.013 kg																								
Warranty	3 years																								
Light		Ordering details																							
Kelvin	3000 K	L024362430	Quantity pc(s)	EAN																					
Colour temp nr	830	Single package	1	8718739058804																					
Stable lumen	180 lm	Inner carton	10	18718739058801																					
Color Rendering Index (CRI)	82	Outer carton	100	28718739058808																					



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)



21-07-2025