



PROFESSIONAL  
LIGHTING

### L025365030

LED GX53 74x27mm 230V 650Lm 7W  
3000K 830 120° AC Opal Dimmable

### Household, Disc GX53 Premium



General		Energy																							
Epel registration no	1811211	Operating voltage		230 V																					
Socket	GX53	Volt		220..240 V																					
Width	74.00 mm	Frequency		50..60 Hz																					
Depth	74.00 mm	Watt		7 W																					
Height	27.00 mm	Current type		AC																					
Finish	Opal	Power factor		0.9																					
Colour	White	Energy efficiency class		F																					
Colour housing	White	Energy consumption		7 W																					
Body material	Polycarbonat	Lamp efficacy		92.86																					
Lifespan	15000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">14</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD 2835		Dimm type	Trailing and leading edge		Number of leds / sticks	14		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD 2835																								
Dimm type	Trailing and leading edge																								
Number of leds / sticks	14																								
Colour consistency SDCM	SDCM5																								
Dim to warm	No																								
Adjustable beam angle	No																								
Switches	50000																								
Beam angle	120 °																								
Dimmable	Yes																								
Degree of protection	IP20																								
Net weight	0.038 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	3000 K	L025365030	Quantity pc(s)	EAN																					
Colour temp nr	830	Single package	1	8718739071308																					
Stable lumen	650 lm	Inner carton	10	18718739071305																					
Lumen 120 cone	550 lm	Outer carton	100	28718739071302																					
Luminous intensity	580 cd																								
Color Rendering Index (CRI)	80																								



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionallighting](#) | [schiefersignaal](#)

04-06-2025