



PROFESSIONAL
LIGHTING

L025365030

LED GX53 74x27mm 230V 650Lm 7W
3000K 830 120° AC Opal Dimmable

Household, Disc GX53 Premium



General		Energy																						
Eprel registration no	1811211	Operating voltage	230 V																					
Socket	GX53	Volt	220..240 V																					
Width	74.00 mm	Frequency	50..60 Hz																					
Depth	74.00 mm	Watt	7 W																					
Height	27.00 mm	Current type	AC																					
Finish	Opal	Power factor	0.9																					
Colour	White	Energy efficiency class	F																					
Colour housing	White	Energy consumption	7 W																					
Body material	Polycarbonat	Lamp efficacy	92.86																					
Lifespan	15000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">14</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>		Filament LED	No		LED type	SMD 2835		Dimm type	Trailing and leading edge		Number of leds / sticks	14		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																							
LED type	SMD 2835																							
Dimm type	Trailing and leading edge																							
Number of leds / sticks	14																							
Colour consistency SDCM	SDCM5																							
Dim to warm	No																							
Adjustable beam angle	No																							
Switches	50000																							
Beam angle	120 °																							
Dimmable	Yes																							
Degree of protection	IP20																							
Net weight	0.038 kg																							
Warranty	2 years																							
Light		Ordering details																						
Kelvin	3000 K	L025365030	Quantity pc(s)	EAN																				
Colour temp nr	830	Single package	1	8718739071308																				
Stable lumen	650 lm	Inner carton	10	18718739071305																				
Lumen 120 cone	550 lm	Outer carton	100	28718739071302																				
Luminous intensity	580 cd																							
Color Rendering Index (CRI)	80																							



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionallighting](#) | [schiefersignaal](#)

05-02-2025