PROFESSIONAL LIGHTING

L028522030-1

LED G8.5 T30x110mm 230V 2000Lm 18W
3000K 830 360° AC Clear Dimmable

Specials & Projects, G8.5 230V Premium





General

Eprel registration no	2434625
Socket	G8.5
Bulb shape	T30
Width	30.00 mm
Depth	30.00 mm
Height	110.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	25000 hours
Switches	15000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.120 kg
Warranty	2 years

Light

CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	2000 lm

Remark

Replace existing lamps with these 230V mains-powered LED's by removing the ballast and connecting the lamp holder on 230V mains Warranty void if used in enclosed luminaires

Energy

Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	18 W
Current type	AC
Power factor	0.95
Energy efficiency class	E
Energy consumption	18 W
Lamp efficacy	111.11

LED

Filament LED	No
LED type	SMD 2835
Dimm type	Trailing and leading edge
Number of leds / sticks	120
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details

L028522030-1	Quantity pc(s)	EAN
Single package	1	8718739081994
Inner carton	10	18718739081991
Outer carton	100	28718739081998

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal