



L141801830

LED E14 Tube T18x80mm 230V 660Lm 6W
3000K 830 360° AC/DC Opal Dimmable

Marine & Industry, Tubular Compact Premium



| General | |
|----------------------|--------------|
| Epel registration no | 832709 |
| Socket | E14 |
| Bulb shape | T18 |
| Width | 18.00 mm |
| Depth | 18.00 mm |
| Height | 80.00 mm |
| Finish | Opal |
| Colour | Colourless |
| Body material | Polycarbonat |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.024 kg |
| Warranty | 3 years |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 6 W |
| Current type | AC/DC |
| Power factor | 0.9 |
| Energy efficiency class | E |
| Energy consumption | 6 W |
| Replacement wattage | 51 W |
| Lamp efficacy | 110.00 |

| LED | |
|-------------------------|---------------------------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 70 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|--------|
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 660 lm |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L141801830 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739063884 |
| Inner carton | 10 | 18718739063881 |
| Outer carton | 100 | 28718739063888 |