



## L144181830

LED E14 Stick T37x108mm 95-265V 810Lm  
7W 3000K 830 270° AC/DC Opal Non-  
Dimmable

## Marine & Industry, Tubular VR 95-265V



| General                     |              | Energy                  |                    |
|-----------------------------|--------------|-------------------------|--------------------|
| Epel registration no        | 1646503      | Volt                    | 95..265 V          |
| Socket                      | E14          | Frequency               | 50..60 Hz          |
| Bulb shape                  | T38          | Watt                    | 7 W                |
| Width                       | 37.00 mm     | Current type            | AC/DC              |
| Depth                       | 37.00 mm     | Power factor            | 0.5                |
| Height                      | 108.00 mm    | Energy efficiency class | E                  |
| Finish                      | Opal         | Energy consumption      | 7 W                |
| Colour                      | White        | Replacement wattage     | 60 W               |
| Colour housing              | White        | Lamp efficacy           | 115.71             |
| Body material               | Polycarbonat | LED                     |                    |
| Lifespan                    | 25000 hours  | Filament LED            | No                 |
| Switches                    | 15000        | LED type                | SMD 2835           |
| Beam angle                  | 270 °        | Dimm type               | Non-Dim            |
| Dimmable                    | No           | Number of leds / sticks | 14                 |
| Degree of protection        | IP20         | Colour consistency SDCM | SDCM5              |
| Net weight                  | 0.038 kg     | Dim to warm             | No                 |
| Warranty                    | 2 years      | Adjustable beam angle   | No                 |
| Light                       |              | Ordering details        |                    |
| Kelvin                      | 3000 K       | L144181830              | Quantity pc(s) EAN |
| Colour temp nr              | 830          | Single package          | 1 8718739070325    |
| Stable lumen                | 810 lm       | Inner carton            | 10 18718739070322  |
| Color Rendering Index (CRI) | 80           | Outer carton            | 100 28718739070329 |