



## L147215004

LED E14 Filament Ball G45x75mm 230V 1W  
360° AC Yellow Non-Dimmable

**Specials & Projects, Party Colour  
Premium**



### General

|                      |             |
|----------------------|-------------|
| Socket               | E14         |
| Bulb shape           | G45         |
| Width                | 45.00 mm    |
| Depth                | 45.00 mm    |
| Height               | 75.00 mm    |
| Finish               | Diffused    |
| Colour               | Yellow      |
| Body material        | Glass       |
| Lifespan             | 25000 hours |
| Switches             | 50000       |
| Beam angle           | 360 °       |
| Dimmable             | No          |
| Degree of protection | IP20        |
| Net weight           | 0.014 kg    |
| Warranty             | 2 years     |

### Energy

|                     |            |
|---------------------|------------|
| Operating voltage   | 230 V      |
| Volt                | 220..240 V |
| Frequency           | 50..60 Hz  |
| Watt                | 1 W        |
| Current type        | AC         |
| Power factor        | 0.4        |
| Energy consumption  | 1 W        |
| Replacement wattage | 7 W        |
| Lamp efficacy       | 60.00      |

### LED

|                         |          |
|-------------------------|----------|
| Filament LED            | Yes      |
| LED type                | Sapphire |
| Dimm type               | Non-Dim  |
| Number of leds / sticks | 1        |
| Stick length            | 38 mm    |
| Stick mounting          | Straight |
| Colour consistency SDCM | SDCM6    |
| Dim to warm             | No       |
| Adjustable beam angle   | No       |

### Ordering details

|                |                |                |
|----------------|----------------|----------------|
| L147215004     | Quantity pc(s) | EAN            |
| Single package | 1              | 8718739049734  |
| Inner carton   | 10             | 18718739049731 |
| Outer carton   | 100            | 28718739049738 |

### Light

|              |       |
|--------------|-------|
| Stable lumen | 60 lm |
|--------------|-------|

