



PROFESSIONAL
LIGHTING

L147225922-1

LED E14 Filament Ball G45x80mm 230V
380Lm 4W 2200K 822 360° AC Clear
Dimmable

Decorative, Ball E14



| General | | Energy | | | | | | | | | | | | | | | | | | | |
|-----------------------------|---------------------------|--|----------------|--------------|-----|----------|---------|-----------|---------------------------|-------------------------|---|--------------|-------|----------------|----------|-------------------------|-------|-------------|----|-----------------------|----|
| Epel registration no | 1132262 | Operating voltage | 230 V | | | | | | | | | | | | | | | | | | |
| Socket | E14 | Volt | 220..240 V | | | | | | | | | | | | | | | | | | |
| Bulb shape | G45 | Frequency | 50..60 Hz | | | | | | | | | | | | | | | | | | |
| Width | 45.00 mm | Watt | 4 W | | | | | | | | | | | | | | | | | | |
| Depth | 45.00 mm | Current type | AC | | | | | | | | | | | | | | | | | | |
| Height | 80.00 mm | Power factor | 0.90 | | | | | | | | | | | | | | | | | | |
| Finish | Clear | Energy efficiency class | F | | | | | | | | | | | | | | | | | | |
| Colour | Colourless | Energy consumption | 4 W | | | | | | | | | | | | | | | | | | |
| Body material | Glass | Replacement wattage | 34 W | | | | | | | | | | | | | | | | | | |
| Lifespan | 15000 hours | Lamp efficacy | 95.00 | | | | | | | | | | | | | | | | | | |
| Switches | 50000 | <div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | Yes | LED type | Ceramic | Dimm type | Trailing and leading edge | Number of leds / sticks | 4 | Stick length | 38 mm | Stick mounting | Straight | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | Yes | | | | | | | | | | | | | | | | | | | | |
| LED type | Ceramic | | | | | | | | | | | | | | | | | | | | |
| Dimm type | Trailing and leading edge | | | | | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 4 | | | | | | | | | | | | | | | | | | | | |
| Stick length | 38 mm | | | | | | | | | | | | | | | | | | | | |
| Stick mounting | Straight | | | | | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | | | | | |
| Beam angle | 360 ° | | | | | | | | | | | | | | | | | | | | |
| Dimmable | Yes | | | | | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | | | | | |
| Net weight | 0.015 kg | | | | | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | | | | | |
| Light | | Ordering details | | | | | | | | | | | | | | | | | | | |
| Kelvin | 2200 K | L147225922-1 | Quantity pc(s) | | | | | | | | | | | | | | | | | | |
| Colour temp nr | 822 | Single package | 1 | | | | | | | | | | | | | | | | | | |
| Stable lumen | 380 lm | Inner carton | 10 | | | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 82 | Outer carton | 60 | | | | | | | | | | | | | | | | | | |
| | | | EAN | | | | | | | | | | | | | | | | | | |
| | | | 8718739066540 | | | | | | | | | | | | | | | | | | |
| | | | 18718739066547 | | | | | | | | | | | | | | | | | | |
| | | | 28718739066544 | | | | | | | | | | | | | | | | | | |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

24-12-2024