



PROFESSIONAL  
LIGHTING

### L147225922-1

LED E14 Filament Ball G45x80mm 230V  
380Lm 4W 2200K 822 360° AC Clear  
Dimmable

### Decorative, Ball E14



General		Energy																			
Epel registration no	1132262	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	4 W																		
Depth	45.00 mm	Current type	AC																		
Height	80.00 mm	Power factor	0.90																		
Finish	Clear	Energy efficiency class	F																		
Colour	Colourless	Energy consumption	4 W																		
Body material	Glass	Replacement wattage	34 W																		
Lifespan	15000 hours	Lamp efficacy	95.00																		
Switches	50000	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Straight</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Straight	Colour consistency SDCM	SDCM6	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Straight																				
Colour consistency SDCM	SDCM6																				
Dim to warm	No																				
Adjustable beam angle	No																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.015 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L147225922-1</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739066540</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739066547</td></tr><tr><td>Outer carton</td><td>60</td><td>28718739066544</td></tr></table>		L147225922-1	Quantity pc(s)	EAN	Single package	1	8718739066540	Inner carton	10	18718739066547	Outer carton	60	28718739066544						
L147225922-1	Quantity pc(s)			EAN																	
Single package	1			8718739066540																	
Inner carton	10			18718739066547																	
Outer carton	60			28718739066544																	
Kelvin	2200 K																				
Colour temp nr	822																				
Stable lumen	380 lm																				
Color Rendering Index (CRI)	82																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

04-06-2025