



L147235012

LED E14 Filament Ball Top Mirror
G45x75mm 230V 350Lm 4W 2500K 825
360° AC Silver Dimmable

Decorative, Top Mirror



| General | |
|-----------------------|-------------|
| Eprel registration no | 765843 |
| Socket | E14 |
| Bulb shape | G45 |
| Width | 45.00 mm |
| Depth | 45.00 mm |
| Height | 75.00 mm |
| Finish | Clear |
| Colour | Silver |
| Body material | Glass |
| Mirroring type | Top |
| Lifespan | 15000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.017 kg |
| Warranty | 2 years |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 4 W |
| Replacement wattage | 32 W |
| Lamp efficacy | 87.50 |

| LED | |
|-------------------------|---------------------------|
| Filament LED | Yes |
| LED type | Ceramic |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 4 |
| Stick length | 38 mm |
| Stick mounting | Twisted |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|--------|
| Kelvin | 2500 K |
| Colour temp nr | 825 |
| Stable lumen | 350 lm |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L147235012 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739065321 |
| Inner carton | 10 | 18718739065328 |
| Outer carton | 100 | 28718739065325 |

