



L147239930

LED E14 Ball G45x80mm 12-60V 250Lm
3W 3000K 830 160° DC Opal Non-
Dimmable

**Marine & Industry, General VR 12-60V
Premium**



General		Energy																							
Eprel registration no	831301	Volt		12..60 V																					
Socket	E14	Frequency		50 Hz																					
Bulb shape	G45	Watt		3 W																					
Width	45.00 mm	Current type		DC																					
Depth	45.00 mm	Power factor		1																					
Height	80.00 mm	Energy efficiency class		G																					
Finish	Opal	Energy consumption		3 W																					
Colour	White	Replacement wattage		25 W																					
Colour housing	White	Lamp efficacy		83.33																					
Body material	Polycarbonat	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD</td></tr><tr><td>Dimm type</td><td colspan="2">Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">5</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD		Dimm type	Non-Dim		Number of leds / sticks	5		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD																								
Dimm type	Non-Dim																								
Number of leds / sticks	5																								
Colour consistency SDCM	SDCM5																								
Dim to warm	No																								
Adjustable beam angle	No																								
Lifespan	25000 hours																								
Switches	50000																								
Beam angle	160 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.015 kg																								
Warranty	3 years																								
Light		Ordering details																							
Kelvin	3000 K	L147239930	Quantity pc(s)	EAN																					
Colour temp nr	830	Single package	1	8718739055490																					
Stable lumen	250 lm	Inner carton	10	18718739055497																					
Color Rendering Index (CRI)	82	Outer carton	100	28718739055494																					