

**L147247011**

LED E14 Filament DimToWarm Ball  
G45x75mm 230V 320Lm 4W 2000-2700K  
920-927 360° AC Opal Dimmable

Household, Dim To Warm



General		Energy																			
Eprel registration no	1988866	Operating voltage	230 V																		
Socket	E14	Volt	220..240 V																		
Bulb shape	G45	Frequency	50..60 Hz																		
Width	45.00 mm	Watt	4 W																		
Depth	45.00 mm	Current type	AC																		
Height	75.00 mm	Power factor	0.85																		
Finish	Opal	Energy efficiency class	G																		
Colour	White	Energy consumption	4 W																		
Colour housing	White	Replacement wattage	30 W																		
Body material	Glass	Lamp efficacy	80.00																		
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Ceramic</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>4</td></tr><tr><td>Stick length</td><td>38 mm</td></tr><tr><td>Stick mounting</td><td>Twisted</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>Yes</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Ceramic	Dimm type	Trailing and leading edge	Number of leds / sticks	4	Stick length	38 mm	Stick mounting	Twisted	Colour consistency SDCM	SDCM6	Dim to warm	Yes	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Ceramic																				
Dimm type	Trailing and leading edge																				
Number of leds / sticks	4																				
Stick length	38 mm																				
Stick mounting	Twisted																				
Colour consistency SDCM	SDCM6																				
Dim to warm	Yes																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.010 kg																				
Warranty	2 years																				
Light		<div>Ordering details</div> <table><tr><td>L147247011</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739071704</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739071701</td></tr><tr><td>Outer carton</td><td>100</td><td>28718739071708</td></tr></table>		L147247011	Quantity pc(s)	EAN	Single package	1	8718739071704	Inner carton	10	18718739071701	Outer carton	100	28718739071708						
L147247011	Quantity pc(s)			EAN																	
Single package	1			8718739071704																	
Inner carton	10			18718739071701																	
Outer carton	100			28718739071708																	
Kelvin	2000..2700 K																				
Colour temp nr	920..927																				
Stable lumen	320 lm																				
Color Rendering Index (CRI)	93																				