



L148518830

LED E14 Tube T18x90mm 230V 300lm 4W
3000K 830 360° AC Opal Non-Dimmable

**Marine & Industry, Tubular Compact
Premium**



General		Energy																							
Eprel registration no	580361	Operating voltage	230 V																						
Socket	E14	Volt	220..240 V																						
Bulb shape	T18	Frequency	50..60 Hz																						
Width	18.00 mm	Watt	4 W																						
Depth	18.00 mm	Current type	AC																						
Height	90.00 mm	Power factor	0.4																						
Finish	Opal	Energy consumption	4 W																						
Colour	Colourless	Replacement wattage	28 W																						
Body material	Polycarbonat	Lamp efficacy	75.00																						
Lifespan	25000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD</td></tr><tr><td>Dimm type</td><td colspan="2">Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">26</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM6</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD		Dimm type	Non-Dim		Number of leds / sticks	26		Colour consistency SDCM	SDCM6		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD																								
Dimm type	Non-Dim																								
Number of leds / sticks	26																								
Colour consistency SDCM	SDCM6																								
Dim to warm	No																								
Adjustable beam angle	No																								
Switches	15000																								
Beam angle	360 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.017 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	3000 K	L148518830	Quantity pc(s)	EAN																					
Colour temp nr	830	Single package	1	8718739060951																					
Stable lumen	300 lm	Inner carton	10	18718739060958																					
Luminous intensity	45 cd	Outer carton	100	28718739060955																					
Color Rendering Index (CRI)	80																								