

L149135019

LED E14 Filament Candle C35x98mm 230V
250Lm 4.5W 1900K 819 360° AC Flame
Dimmable

Decorative, Flame


| General | |
|-----------------------|-------------|
| Eprel registration no | 831318 |
| Socket | E14 |
| Bulb shape | C35 |
| Width | 35.00 mm |
| Depth | 35.00 mm |
| Height | 98.00 mm |
| Finish | Flame |
| Colour | Colourless |
| Body material | Glass |
| Lifespan | 15000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.012 kg |
| Warranty | 2 years |

| Light | |
|-----------------------------|--------|
| Kelvin | 1900 K |
| Colour temp nr | 819 |
| Stable lumen | 250 lm |
| Color Rendering Index (CRI) | 80 |

| Energy | | |
|-------------------------|--|------------|
| Operating voltage | | 230 V |
| Volt | | 220..240 V |
| Frequency | | 50..60 Hz |
| Watt | | 4.5 W |
| Current type | | AC |
| Power factor | | 0.85 |
| Energy efficiency class | | G |
| Energy consumption | | 5 W |
| Replacement wattage | | 25 W |
| Lamp efficacy | | 55.56 |

| LED | |
|-------------------------|---------------------------|
| Filament LED | Yes |
| LED type | Ceramic |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 4 |
| Stick length | 38 mm |
| Stick mounting | Twisted |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|------------------|----------------|----------------|
| L149135019 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739059351 |
| Inner carton | 10 | 18718739059358 |
| Outer carton | 100 | 28718739059355 |